

THIS MATERIAL SAFETY DATA SHEET MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200 AND ANSI Z400-1-1998.

1. PRODUCT AND COMPANY IDENTIFICATION: 10/23/08

PRODUCT CODE: VG-R-127
TRADE NAME: PAINT CORRECTION BAR
PRODUCT DESCRIPTION: CLAY BAR (LAVENDER)
GENERAL USE: PAINT OVERSPRAY REMOVER

MANUFACTURER: Automotive International
ADDRESS: 8855 Blue Ash Road
Cincinnati, Ohio 45242
PHONE NUMBER: (513) 489-7883 (8am-5pm m-f)
FAX NUMBER: (513) 489-1329
CHEMTREC: (800) 424-9300 (24 HOUR)
OUTSIDE U.S. (703) 527-3887

2. COMPOSITION INFORMATION ON INGREDIENTS:

COMPONENT	CAS#	WT%
1. CALCIUM CARBONATE	1317-65-3	65-95
2. TITANIUM DIOXIDE	13463-67-7	0-5
3. ZINC SULFIDE	1314-98-3	0-5

HAZARDOUS COMPONENTS (OSHA 29CFR 1910.1200)

3. HAZARDS IDENTIFICATION:

EMERGENCY OVERVIEW: Solid clay bar, Lavender color.
May be irritating to eyes with prolonged contact.
INHALATION: None known.
EYE CONTACT: Irritating, but will not permanently injure eye tissue.
SKIN CONTACT: None known.
INGESTION: Irritation, & nausea.
CHRONIC: None known

4. FIRST AID MEASURES:

INHALATION: Move to fresh air.
EYE CONTACT: Rinse with water for 15 minutes. Get medical attention if irritation persists.
SKIN CONTACT: Wash with soap and water. Rinse thoroughly.
INGESTION: Do not induce vomiting. Give glass of water. Get medical attention.
POTENTIAL ENVIRONMENTAL EFFECTS: None known.

5. FIRE FIGHTING MEASURES:

Flashpoint and Method: > 200 f (> 94 c) (TCC)
Flammable Limits: Not Available
Auto-ignition Temperature: Not Available

HAZARDOUS COMBUSTION PRODUCTS: Possible oxides of carbon.
FIRE FIGHTING INSTRUCTIONS: Use water mist to cool fire exposed drum.
FIRE FIGHTING EQUIPMENT: Bunker gear and SCBA.

6. ACCIDENTAL RELEASE MEASURES:
LAND SPILL: Dispose of properly.

WATER SPILL: N/A

7. HANDLING AND STORAGE:
HANDLING - TAKE NORMAL CARE TO PREVENT PROLONGED SKIN CONTACT.
STORAGE - KEEP FROM HEATING ABOVE 110°F. STORE IN ORIGINAL CONTAINER.

8. EXPOSURE CONTROL/PERSONAL PROTECTION:
ENGINEERING CONTROLS: The use of mechanical ventilation is not needed under normal conditions.
PERSONAL PROTECTION: Not need under normal conditions. However for prolonged contact the use of rubber/latex gloves is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES:
VAPOR PRESSURE: Not determined
SPECIFIC GRAVITY: 2.4 @ 70°F
SOLUBILITY IN WATER: Insoluble
PH: N/A
BOILING POINT: Not Available
VISCOSITY: Not Applicable
EVAPORATION RATE: Slower than water (n-Butyl Acetate=1)
FREEZING POINT: Not Available
ODOR: Bland
APPEARANCE: Lavender clay bar
PHYSICAL STATE: Solid
FLASH POINT: Will not flash
VOC%: 0 g/Liter (Calculated)

10. STABILITY AND REACTIVITY:
GENERAL: This product is stable and hazardous polymerization will not occur.
INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID: None known.
HAZARDOUS DECOMPOSITION: None known.

11. TOXICOLOGICAL INFORMATION: The complete toxicological data for each Ingredient is beyond the scope of this document.

12. ECOLOGICAL INFORMATION:
ECOTOXIOLOGICAL INFORMATION: None known.

13. DISPOSAL CONSIDERATION:
Please refer to Sections 5,6, and 15 for disposal and regulatory information.

14. TRANSPORTATION INFORMATION:
DOT Shipping description: Unrestricted/Non-regulated.

15. REGULATORY INFORMATION:
TSCA (Toxic Substance Control Act): All components are listed on the TSCA.
CERCLA: Not reportable
SARA Title III: No known reportable ingredients.

16. OTHER INFORMATION:
NFPA RATING: Health-0,Fire-1,Reactivity-0
KEY: 4=Severe,3=Serious,2=Moderate,1=Slight,0=Minimal

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSON PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN HIS USE OF THE MATERIAL.