

aero rust AJ

- M A T E R I A L S A F E T Y D A T A S H E E T

- SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION -

PRODUCT NAME : VG101A VALUGUARD RUST PREVENTA
IDENTIFICATION NUMBER: A-8086 (0035) DATE PRINTED: 10/12/06
PRODUCT USE/CLASS : RUST PREVENTATIVE

MANUFACTURED FOR:
AUTOMOTIVE INTERNATIONAL, INC.
11308 TAMARCO DRIVE
CINCINNATI, OHIO 45242
PHONE: 1-800-543-7156

MANUFACTURED BY:
AUTOMOTIVE INTERNATIONAL, INC.
11308 TAMARCO DRIVE
CINCINNATI, OHIO 45242
PHONE: 1-800-543-7156

EMERGENCY TELEPHONE: 800-543-7156
MON - FRI /8:00 AM-5:00 PM

EMERGENCY TELEPHONE: 800-543-7156
MON - FRI /8:00 AM-5:00 PM

PREPARER: , PHONE: , PREPARE DATE: 10/12/06 8-1-07

- SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS -

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	CALCIUM SULFONATE	61789-86-4	45.0 %
02	N-HEXANE	110-54-3	30.0 %
03	PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	25.0 %
04	HYDROTREATED KEROSENE	64742-47-8	5.0 %
05	STODDARD SOLVENT	8052-41-3	5.0 %
06	SYNTHETIC ISOPARAFFINIC HYDROCARBON	90622-57-4	5.0 %

ITEM	EXPOSURE LIMITS				COMPANY TLV-TWA	SKIN
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING		
01	N. E.	N. E.	N. E.	N. E.	N. E.	NO
02	50 PPM	N. E.	50 PPM	500 PPM	N. E.	YES
03	1000 PPM	N. E.	800 PPM	N. E.	N. E.	YES
04	N. E.	N. E.	N. E.	N. E.	N. E.	NO
05	100 PPM	N. E.	100 PPM	500 PPM	N. E.	YES
06	N. E.	N. E.	N. E.	N. E.	300 PPM	NO

(See Section 16 for abbreviation legend)

(Continued on Page 2)

Product: A-8086 (0035) Preparation Date: 10/12/06 Page 2

- SECTION 3 - HAZARDS IDENTIFICATION -

*** EMERGENCY OVERVIEW ***: Vapors irritating to eyes and respiratory tract. Vapors may cause flash fire or explosion.

aero rust AJ

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

EFFECTS OF OVEREXPOSURE - INHALATION: Headaches, dizziness, nausea, decreased blood pressure, changes in heart rate and cyanosis may result from over-exposure to vapor or skin exposure. Prolonged inhalation may be harmful.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be harmful or fatal if swallowed. If a Corrosive product, may cause severe and permanent damage to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause nervous system damage. Overexposure may cause lung damage. Overexposure may cause kidney damage. May cause liver disorder (e.g., edema, proteinuria) and damage.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION
INGESTION EYE CONTACT

- SECTION 4 - FIRST AID MEASURES -

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: Get medical attention immediately. If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

(Continued on Page 3)

Product: A-8086 (0035) Preparation Date: 10/12/06 Page 3

- SECTION 5 - FIRE FIGHTING MEASURES -

FLASH POINT: -156 F LOWER EXPLOSIVE LIMIT: 0.7 %
(SETAFLASH CLOSED CUP) UPPER EXPLOSIVE LIMIT: 9.6 %

FLAME EXTENSION (STREAM): 24" TO 30"
FLAME EXTENSION (MIST): 16" TO 20"
EXTREMELY FLAMMABLE: 6 " FLASH BACK

AUTOIGNITION TEMPERATURE: ND

aero rust AJ

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly banded and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

- SECTION 6 - ACCIDENTAL RELEASE MEASURES -

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

- SECTION 7 - HANDLING AND STORAGE -

HANDLING: Wash thoroughly after handling.

STORAGE: Keep away from heat, sparks and flame. Keep from freezing.

- SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION -

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed

(Continued on Page 4)

Product: A-8086 (0035) Preparation Date: 10/12/06 Page 4

- SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION -

exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

aero rust AJ

OTHER PROTECTIVE EQUIPMENT: STANDARD INDUSTRIAL CLOTHING STANDARDS SHOULD BE FOLLOWED.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/Label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

- SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -

BOILING RANGE : -43 - 387 F VAPOR DENSITY : Is heavier than air
ODOR : SOLVENT ODOR THRESHOLD : ND
APPEARANCE : AMBER EVAPORATION RATE: Is faster than Butyl
SOLUBILITY IN H2O : NEGLIGIBLE Acetate
FREEZE POINT : 32 SPECIFIC GRAVITY: 0.6011
VAPOR PRESSURE : 80-90 pH @ 0.0 % : NA
PHYSICAL STATE : AEROSOL VISCOSITY : NA
COEFFICIENT OF WATER/OIL DISTRIBUTION: NEGLIGIBLE

(See Section 16 for abbreviation legend)

- SECTION 10 - STABILITY AND REACTIVITY -

CONDITIONS TO AVOID: ALL SOURCES OF IGNITION, WELDING ARCS, AND OPEN FLAMES.

INCOMPATIBILITY: STRONG ACIDS, ALKALIS, OXIDIZERS, AND AMINES.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, OXIDES OF NITROGEN, AND MAY PRODUCE FORMS OF CHLORIDE, CHLORINE, AND PHOSGENE.

(Continued on Page 5)

Product: A-8086 (0035) Preparation Date: 10/12/06 Page 5

- SECTION 10 - STABILITY AND REACTIVITY -

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

- SECTION 11 - TOXICOLOGICAL PROPERTIES -

PRODUCT LD50: 20 mg/kg PRODUCT LC50: 5500 ppm

COMPONENT TOXICOLOGICAL INFORMATION:

----- CHEMICAL NAME -----	----- LD50 -----	----- LC50 -----
CALCIUM SULFONATE	>20MG/KG/RAT	NE
N-HEXANE	28710 MG/KG/RAT	150000 MG/M3/MOUSE
PROPANE/ISOBUTANE/N-BUTANE	NE	658000 MG/M3/4HRAT
HYDROTREATED KEROSENE	ND	ND
STODDARD SOLVENT	>5000 MG/KG/RAT	>5500 MG/M3/4H/RAT
SYNTHETIC ISOPARAFFINIC HYDROCARBON	>10000 MG/KG/RAT	>12200MG/M3/4H/RAT

1-METHOXY-2-PROPANOL
IRON OXIDE PIGMENTS

aero rust AJ
11700 MG/KG/MOUSE 10000 PPM/5H/RAT
TDLO 135 MG/KG/RAT LO 500UG/M3/24H/61

- SECTION 12 - ECOLOGICAL INFORMATION -

ECOLOGICAL INFORMATION: No Information.

- SECTION 13 - DISPOSAL CONSIDERATIONS -

DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.

- SECTION 14 - TRANSPORTATION INFORMATION -

DOT PROPER SHIPPING NAME: CONSUMER COMMODITY

DOT TECHNICAL NAME: ORM-D

DOT HAZARD CLASS: 2.1

HAZARD SUBCLASS:

DOT UN/NA NUMBER: UN1950

PACKING GROUP:

RESP. GUIDE PAGE: 126

(Continued on Page 6)

Product: A-8086 (0035) Preparation Date: 10/12/06

Page 6

- SECTION 14 - TRANSPORTATION INFORMATION -

- SECTION 15 - REGULATORY INFORMATION -

U. S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

-----	CHEMICAL NAME	-----	CAS NUMBER	WT/WT % IS LESS THAN
	N-HEXANE		110-54-3	30.0 %

aero rust AJ

*** THIS MSDS IS NOT FOR REPRODUCTION OR DISTRIBUTION ***
The information contained on this MSDS is been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

<END OF MSDS>