

THIS MATERIAL SAFETY DATA SHEET MAY BE USED TO COMPLY WITH OSHA'S HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200 AND ANSI Z400-1-1998.

1. PRODUCT AND COMPANY IDENTIFICATION:

10/23/08

PRODUCT CODE: VG-102
TRADE NAME: VALUGARD PAINT SEALANT
PRODUCT DESCRIPTION: MIXTURE OF HYDROCARBONS AND RESINS
GENERAL USE: AUTOMOTIVE PAINT SEALANT

MANUFACTURER: AUTOMOTIVE INTERNATIONAL
ADDRESS: 8855 Blue Ash Road
CINCINNATI, OHIO 45242
PHONE NUMBER: (513) 489-7883 (8am-5pm m-f)
FAX NUMBER: (513) 489-1329
CHEMTREC: (800) 424-9300 (24 HOUR)
OUTSIDE U.S. (703) 527-3887

2. COMPOSITION INFORMATION ON INGREDIENTS:

COMPONENT	CAS#	WT%
ALIPHATIC HYDROCARBON	8052-41-3	5-15
HYDROTREATED LIGHT DISTILLATE	64742-47-8	5-10
METHANOL	67-56-1	.5-1

HAZARDOUS COMPONENTS (OSHA 29CFR 1910.1200)

ALIPHATIC HYDROCARBON OSHA PEL - 100 ppm & ACGIH - 100 ppm
HYDROTREATED LIGHT DISTILLATE OSHA PEL & ACGIH - TWA 400 ppm
METHANOL OSHA PEL & ACGIH - 20 ppm

VOC COMPLIANT: 12/8/04

3. HAZARDS IDENTIFICATION:

EMERGENCY OVERVIEW: Semi viscous liquid, solvent odor.

May be irritating to skin and eyes with prolonged contact.

INHALATION: None known.

EYE CONTACT: Irritating, but will not permanently injure eye tissue.

SKIN CONTACT: Frequent or prolonged contact may irritate skin, & dryness.

INGESTION: Overexposure by ingestion may injure your liver or kidney.

CHRONIC: None known

4. FIRST AID MEASURES:

INHALATION: None known.

EYE CONTACT: Rinse with water for 15 minutes. Get medical attention if irritation persists.

SKIN CONTACT: Wash with soap and water. Rinse thoroughly.

INGESTION: Do not induce vomiting. Get medical attention.

POTENTIAL ENVIRONMENTAL EFFECTS: None known.

5. FIRE FIGHTING MEASURES:

Flashpoint and Method: 142°F/61.1°C TCC
Flammable Limits: LEL- 0.8 UEL- 5.0
Auto-ignition Temperature: Not Available

HAZARDOUS COMBUSTION PRODUCTS: Possible oxides of carbon.

FIRE FIGHTING INSTRUCTIONS: Use water mist to cool fire exposed drum.

FIRE FIGHTING EQUIPMENT: Bunker gear and SCBA

6. ACCIDENTAL RELEASE MEASURES:

LAND SPILL: Avoid runoff into storm sewers or ditches by containment with sand or absorbent material.

WATER SPILL: Remove from with suitable absorbent materials.

7. HANDLING AND STORAGE:

HANDLING - TAKE NORMAL CARE TO PREVENT PROLONGED SKIN CONTACT.

STORAGE - KEEP FROM FREEZING OR FROM HEATING ABOVE 120°F. STORE IN ORIGINAL CONTAINER.

8. EXPOSURE CONTROL/PERSONAL PROTECTION:

ENGINEERING CONTROLS: The use of mechanical ventilation is not needed under normal conditions.

PERSONAL PROTECTION: Not need under normal conditions. However for prolonged contact use rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES:

VAPOR PRESSURE: Not determined

SPECIFIC GRAVITY: 1.00 @ 70°F

SOLUBILITY IN WATER: Insoluble

PH: Not Available

BOILING POINT: Not Available

VISCOSITY: 8,000 -9,800 cps (spindle 5 @ 20 rpm) @ 70°F

EVAPORATION RATE: .1 (n-Butyl Acetate=1)

FREEZING POINT: Not Available

ODOR: Solvent

APPEARANCE: Semi-viscous light tan cream

PHYSICAL STATE: Creamy Liquid

FLASH POINT: 142°F/61.1°C

VOC%: 150 g/Liter (Calculated)

10. STABILITY AND REACTIVITY:

GENERAL: This product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID: Strong Oxidizers

HAZARDOUS DECOMPOSITION: None

11. TOXICOLOGICAL INFORMATION: The complete toxicological data for each ingredient is beyond the scope of this document.

12. ECOLOGICAL INFORMATION:

ECOTOXICOLOGICAL INFORMATION: None available.

13. DISPOSAL CONSIDERATION:

Please refer to Sections 5,6, and 15 for disposal and regulatory information.

14. TRANSPORTATION INFORMATION:

DOT Shipping description: Unrestricted/Non-regulated

15. REGULATORY INFORMATION:

TSCA (Toxic Substance Control Act): All components are listed on the TSCA.

CERCLA: Not reportable

SARA Title III: No known reportable ingredients.

16. OTHER INFORMATION:

NFPA RATING: Health-1, Fire-2, Reactivity-0

KEY: 4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSON PROXIMATELY CAUSED BY THE MATERIAL IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN HIS USE OF THE MATERIAL.